

CHECK VALVES



CHECK VALVES

CONSTRUCTION	•CA360 Brass	
APPLICATIONS	•Unidirectional Flow Applications	
	•Maximum Pressure :	
RANGES	1500 PSIG	
	•Temperature:	
	-40° F to +300° F (Standard)	^
	-40° F to +400° F (Special)	\triangle

FEATURES/BENEFITS

•Self Centering Seal Design

•O-Ring Soft Seat / Metal Back Up Seat

Zero Leakage

•1/3 PSI Cracking Pressure Standard

Optional Cracking Pressures Available

Made in USA

Guaranteed Quality



NOTES

- Parts that include "PBF" are supplied as low lead compliant.
- Part numbers without the "PBF" distinction are NOT lead free complaint.
- Non-stock items and special parts are available on a quotation basis.
- Configurations and dimensions are subject to change without notice.

*We encourage specials! If you don't see a configuration available in our catalog don't be discouraged, please contact our sales team directly so we can make sure you're getting the best valve for your application. Email sales@robo-fit.com with details.





CHECK VALVES

741CV MPTF x MPTF

PART NUMBER	MPTF	MPTF
741CV-J	1/8"	1/8"



751CV MPT x MPT

PART NUMBER	MPT	MPT
751CV-JXJ	1/8"	1/8"
751CV-LXL	1/4"	1/4"
751CV-NXN	3/8"	3/8"
751CV-PXP	1/2"	1/2"




745CV FLARE x MPTF

PART NUMBER	FLARE	MPTF
745CV-4J	1/4"	1/8"
745CV-J4	1/8"	1/4"



752CV FPT x FPT





750CV1 MPT x FPT

PART NUMBER	MPT	FPT
750CV1-JXJ	1/8"	1/8"
750CV1-LXL	1/4"	1/4"
750CV1-NXN	3/8"	3/8"
750CV1-PXP	1/2"	1/2"



750CV2 FPT x MPT

PART NUMBER	FPT	MPT
750CV2-JXJ	1/8"	1/8"
750CV2-LXL	1/4"	1/4"
750CV2-NXN	3/8"	3/8"
750CV2-PXP	1/2"	1/2"



