





AIR BRAKE HOSE

CONSTRUCTION	•Tube: EPDM, RMA Class C
	•Cover: EPDM, RMA Class C
APPLICATIONS	•Reinforcement: Spiral Polyester Yarn
	•Cover Color: Black
RANGES	• Air Brake Systems 
	•Temperature Range: -40°F to 200°F  -40°C to +93°C

Layline Text Reads:
Air Brake 3/8" A SAE J1402 Made In USA D.O.T. KX 3/8 (9.5mm) A
Air Brake 1/2" SP A SAE J1402 Made In USA D.O.T. KX 1/2 SP (12.7mm) A

AIR BRAKE, TYPE A -SAE J1402 & DOT FMVSS 106

- Designed for conveying air in truck and trailer brake systems.
- Meets D.O.T. FMVSS 106 and SAE J1402A requirements.
- The EPDM tube and cover with the 4-spiral reinforcement make this hose virtually kink proof.

PART NUMBER	NOMINAL I.D.	NOMINAL O.D.	REINFORCEMENT SPIRALS	WORKING PRESSURE	MIN. BEND RADIUS	REEL SIZE
J1402-250HR-06-BK	3/8" 9.53mm	0.75 19.05mm	4	Min. Burst 900PSI (Mpa 6.20)	2.25" 57.15mm	250FT
J1402-250HR-08-BK	1/2" 12.70mm	0.88 22.23mm	4	Min. Burst 900PSI (Mpa 6.20)	3.00" 76.20mm	250FT